



SAFETY DATA SHEET TRANSPORT ULTRA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name TRANSPORT ULTRA

Product number SPR007/10

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Water conditioning agent and surfactant.

1.3. Details of the supplier of the safety data sheet

Supplier Headland Amenity Ltd.
1-3 Freeman Court
Jarman Way
Royston
Hertfordshire
SG8 5HW
+44 (0)1763 255550
sds@headlandamenity.com

Contact person Wendy Johnson

1.4. Emergency telephone number

Emergency telephone +44 (0)1763 255550 (09.00 - 17.00 GMT Monday - Friday)

National emergency telephone number 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.

TRANSPORT ULTRA

Precautionary statements

P260 Do not breathe vapour/ spray.
 P280 Wear protective gloves, protective clothing and eye protection.
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.
 Rinse skin with water or shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/ doctor.

Contains

TALLOW ALKYLAMINE ETHOXYLATE, SULPHURIC ACID, ISODECYL ALCOHOL ETHOXYLATE (POE 6), 2-AMINOETHANOL, TRIDECYL ALCOHOL ETHOXYLATE (POE 6), PHOSPHATE ESTER, BUTANOL-NORM

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

TALLOW ALKYLAMINE ETHOXYLATE	10-30%
CAS number: 61791-26-2 EC number: 500-153-8	
M factor (Acute) = 1 M factor (Chronic) = 1	
Classification	
Acute Tox. 4 - H302	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	
SULPHURIC ACID	10-30%
CAS number: 7664-93-9 EC number: 231-639-5	
Classification	
Skin Corr. 1A - H314	
Eye Dam. 1 - H318	
ISODECYL ALCOHOL ETHOXYLATE (POE 6)	5-10%
CAS number: 78330-20-8 EC number: 616-607-4	
M factor (Acute) = 1	
Classification	
Acute Tox. 4 - H302	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Aquatic Acute 1 - H400	

TRANSPORT ULTRA

2-AMINOETHANOL	5-10%
CAS number: 141-43-5	EC number: 205-483-3
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
STOT SE 3 - H335	
2,2'-OXYBISETHANOL	5-10%
CAS number: 111-46-6	EC number: 203-872-2
Classification	
Acute Tox. 4 - H302	
STOT RE 2 - H373	
TRIDECYL ALCOHOL ETHOXYLATE (POE 6), PHOSPHATE ESTER	5-10%
CAS number: 9046-01-9	EC number: 618-558-4
Classification	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Aquatic Chronic 2 - H411	
BUTANOL-NORM	1-5%
CAS number: 71-36-3	EC number: 200-751-6
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H302	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
STOT SE 3 - H335, H336	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Get medical attention immediately. Never give anything by mouth to an unconscious person. Rinse mouth. Do not induce vomiting.
Skin contact	Remove contaminated clothing and rinse skin thoroughly with water. Wash skin thoroughly with soap and water. Get medical attention immediately. Wash contaminated clothing before reuse.

TRANSPORT ULTRA

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Information not available.

Ingestion Information not available.

Skin contact Information not available.

Eye contact Information not available.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Powder. Water. Alcohol-resistant foam.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Combustion may yield smoke, oxides of carbon and other products of incomplete combustion. Oxides of sulphur, nitrogen or phosphorus may also be formed. Can be dangerous when exposed to extreme heat and flame. Do not allow water to directly enter storage containers as violent reaction may occur. Responders should consider the need for evacuation based on emitted decomposition products. Flammable hydrogen may be produced on prolonged contact with metals such as aluminium, tin, lead and zinc. Do not breathe mist/vapour/spray.

Hazardous combustion products Oxides of carbon. Oxides of sulphur. Oxides of nitrogen. Oxides of phosphorus.

5.3. Advice for firefighters

Protective actions during firefighting Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Avoid the spillage or runoff entering drains, sewers or watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate area. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain the spillage using bunding. Absorb spillage with non-combustible, absorbent material.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

TRANSPORT ULTRA

Usage precautions	Avoid contact with skin and eyes. Use only outdoors or in a well-ventilated area. Mechanical ventilation or local exhaust ventilation may be required. Use suitable respiratory protection if ventilation is inadequate.
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off immediately all contaminated clothing and wash it before reuse. Remove contaminated clothing and protective equipment before entering eating areas.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame. Store at temperatures above 5°C. Will corrode incompatible metals such as aluminium, copper, zinc and mild steel.
----------------------------	---

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

SULPHURIC ACID

Long-term exposure limit (8-hour TWA): WEL 0.05 mg/m³ mist

2-AMINOETHANOL

Long-term exposure limit (8-hour TWA): WEL 1 ppm 2.5 mg/m³

Short-term exposure limit (15-minute): WEL 3 ppm 7.6 mg/m³

Sk

2,2'-OXYBISETHANOL

Long-term exposure limit (8-hour TWA): WEL 23 ppm 101 mg/m³

BUTANOL-NORM

Short-term exposure limit (15-minute): WEL 50 ppm 154 mg/m³

Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment



Eye/face protection Wear tight-fitting, chemical splash goggles or face shield. Provide eyewash station.

Hand protection Chemical resistant gloves.

Other skin and body protection Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Wash hands thoroughly after handling. Wash promptly if skin becomes contaminated. Remove contaminated clothing and protective equipment before entering eating areas. Wash at the end of each work shift and before eating, smoking and using the toilet. Eye wash facilities and emergency shower must be available when handling this product.

Respiratory protection No specific requirements are anticipated under normal conditions of use. If ventilation is inadequate, suitable respiratory protection must be worn. Protect against spray mists.

TRANSPORT ULTRA

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Golden yellow.
Odour	Fatty.
Odour threshold	No information available.
pH	pH (diluted solution): 2.0-2.5 5% (v/v in water)
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	> 93°C SETA Closed Cup.
Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	1.19-1.20 @ 20°C
Bulk density	No information available.
Solubility(ies)	Soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information	No other relevant information available.
--------------------------	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable under recommended transport or storage conditions.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Flammable hydrogen may be produced on prolonged contact with metals such as aluminium, tin, lead and zinc.
---	--

10.4. Conditions to avoid

Conditions to avoid	Extreme heat/open flame/incompatibles.
----------------------------	--

10.5. Incompatible materials

TRANSPORT ULTRA

Materials to avoid Oxidising agents. Strong acids. Strong alkalis. Susceptible metals such as aluminium, tin, lead and zinc.

10.6. Hazardous decomposition products

Hazardous decomposition products None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE dermal (mg/kg) 5,000.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 146.67

Inhalation No information available.

Ingestion No information available.

Skin contact No information available.

Eye contact No information available.

SECTION 12: Ecological information

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulative potential No information available.

Partition coefficient No information available.

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

TRANSPORT ULTRA

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1760
UN No. (IMDG)	1760
UN No. (ICAO)	1760
UN No. (ADN)	1760

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	CORROSIVE LIQUID, N.O.S. (CONTAINS SULPHURIC ACID, TALLOW ALKYLAMINE ETHOXYLATE)
Proper shipping name (IMDG)	CORROSIVE LIQUID, N.O.S. (CONTAINS SULPHURIC ACID, TALLOW ALKYLAMINE ETHOXYLATE, ISODECYL ALCOHOL ETHOXYLATE (POE 6), TRIDECYL ALCOHOL ETHOXYLATE (POE 6), PHOSPHATE ESTER)
Proper shipping name (ICAO)	CORROSIVE LIQUID, N.O.S. (CONTAINS SULPHURIC ACID, TALLOW ALKYLAMINE ETHOXYLATE)
Proper shipping name (ADN)	CORROSIVE LIQUID, N.O.S. (CONTAINS SULPHURIC ACID, TALLOW ALKYLAMINE ETHOXYLATE)

14.3. Transport hazard class(es)

ADR/RID class	8
ADR/RID classification code	C9
ADR/RID label	8
IMDG class	8
ICAO class/division	8
ADN class	8

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II
ADN packing group	II

14.5. Environmental hazards

TRANSPORT ULTRA

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-A, S-B
ADR transport category	2
Emergency Action Code	2X
Hazard Identification Number (ADR/RID)	80
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Supplier company address updated. Emergency contact details updated. NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	12/07/2021
Revision	5
Supersedes date	19/05/2016
Hazard statements in full	<p>H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.